



Most Widely Accepted and Trusted

ICC-ES Listing Report

ESL-1017

ICC-ES | (800) 423-6587 | (562) 699-0543 | www.icc-es.org

Reissued 06/2018

This listing is subject to renewal 06/2019.

DIVISION: 08 00 00—OPENINGS

SECTION: 08 30 00—SPECIALTY DOORS AND FRAMES

REPORT HOLDER:

OVERHEAD DOOR CORPORATION

EVALUATION SUBJECT:

INSULATED ROLLING SERVICE DOORS



Look for the trusted marks of Conformity!

"2014 Recipient of Prestigious Western States Seismic Policy Council (WSSPC) Award in Excellence"



ICC-ES Evaluation Listing Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.



ICC-ES Listing Report

ESL-1017

Reissued June 2018

This listing is subject to renewal June 2019.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 08 00 00—OPENINGS
Section: 08 30 00—Specialty Doors and Frames

Product Certification System:

The ICC-ES product certification system includes evaluating reports of tests of standard manufactured product, prepared by accredited testing laboratories and provided by the listee, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the listee's quality system.

Product: Insulated Rolling Service Doors

Listee: OVERHEAD DOOR CORPORATION

Evaluation: The Overhead Door Corporation insulated rolling service doors were evaluated when tested in accordance with the following standard:

ASTM E283-04, Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen. ASTM International.

Findings: The insulated rolling service doors have a maximum air infiltration rate of less than 1.0 cfm/ft² based on testing in accordance with ASTM E283, as referenced in the following applicable code edition and section:

- 2015 *International Energy Conservation Code*® (IECC) – Section C402.5.2
- 2012 *International Energy Conservation Code*® (IECC) – Section C402.4.3

Identification:

1. Each insulated rolling service door is identified with a label indicating the listee's name (Overhead Door Corporation) and address, the product name, the listing number (ESL-1017) and when applicable, the listing mark.
2. The report holder's contact information is the following:

OVERHEAD DOOR CORPORATION
2501 SOUTH STATE HIGHWAY 121 BUS., SUITE 200
LEWISVILLE, TEXAS 75067
(469) 549-7144
www.overheaddoor.com

Installation: The product must be installed in accordance with the Overhead Door Corporation's instructions.

Model Names: Overhead Door Model 625 Stormtite™, AP Model 627 Stormtite™, and Wayne Dalton Model 800c ThermoTite™

Conditions of listing:

1. The listing addresses only those findings noted above.
2. Approval is the sole responsibility of the local code official.
3. This listing applies only to the materials tested and as submitted for review by ICC-ES.
4. The Stormtite™ insulated rolling service doors are produced in Lewistown, Pennsylvania and the ThermoTite™ rolling service doors are produced in Dalton, Ohio under a quality-control program with inspections by ICC-ES.