



## ICC-ES Listing Report ESL-1009

Reissued December 2023

This listing is subject to renewal December 2024.

**CSI:** DIVISION: 07 00 00—THERMAL AND MOISTURE PROTECTION  
Section: 07 13 00—Sheet Waterproofing

### Product Certification System:

The ICC-ES product certification system includes evaluating reports of tests of standard manufactured product, prepared by accredited testing laboratories and provided by the listee, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the listee's quality system.

**Product:** Nu-Age Films® – Film 6+

**Listee:** ISI BUILDING PRODUCTS

### Compliance with the following standard:

Nu-Age Films® – Film 6+, when applied in accordance with the manufacturer's installation instructions, conforms to the following standard and has the properties noted in Table 1:

- ASTM D4397-10, Standard Specification for Polyethylene Sheeting for Construction, Industrial, and Agricultural Applications, ASTM International.

### Identification:

1. Packaging of Nu-Age Films® carries a label indicating the manufacturer's name and address, the product name, the thickness of the sheeting, the listing number (ESL-1009), and when applicable, the listing mark.
2. The report holder's contact information is the following:

**ISI BUILDING PRODUCTS**  
**401 TRUCK HAVEN ROAD**  
**EAST PEORIA, ILLINOIS 61611**  
[info@isibp.com](mailto:info@isibp.com)  
[www.isibp.com](http://www.isibp.com)

**Installation:** The product must be installed in accordance with the Insulation Solutions, Inc. installation instructions.

### Conditions of listing:

1. This listing report addresses only conformance with the standard noted above.
2. The product, as listed, is non-color-tinted and translucent. The product has not been evaluated for reflectance, luminous transmittance or heat sealability.
3. Approval of the product's use is the sole responsibility of the local code official.

TABLE 1—PROPERTIES OF NU-AGE FILMS AS APPLICABLE TO ASTM D4397-10

Thickness (inches)	0.0024
Impact Resistance (g)	299
Tensile Strength at Break (length direction) Exceeds 1700 psi	Yes
Tensile Strength at Break (width direction) Exceeds 1200 psi	Yes
Elongation % at Break (length direction) Exceeds 225%	Yes
Elongation % at Break (width direction) Exceeds 350%	Yes
Reflectance	n/a
Luminous Transmittance	n/a
Permeance (Perms)	0.028
Heat Sealability	n/a

For **SI**: 1 inch = 25.4 mm, 1 psi = 0.0069 MPa