



## ICC-ES Listing Report

Reissued May 2024

### ESL-1344

This listing is subject to renewal April 2025.

CSI: DIVISION: 09 00 00—FINISHES  
Section: 09 94 00—Decorative Finishing

#### Product Certification System:

The ICC-ES product-certification system includes evaluating reports of tests of standard manufactured product, prepared by accredited testing laboratories and provided by the listee, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the listee's quality system.

Products: CABINET DOORS

Listee: CLAYTON SUPPLY OF HALEYVILLE I

#### Compliance with the following standard:

- 24 CFR part 3280 [2020 with FR-6149-F-02 (effective date March 15, 2021)], Manufactured Home Construction and Safety Standards, United States Department of Housing and Urban Development.

#### Description of Product:

Clayton Supply of Haleyville I interior finish materials are intended for use in manufactured housing constructed under 24 CFR §3280 for the following: Cabinet doors, which can be manufactured with the following: MDF core or particleboard with paper or vinyl laminate for use as panel inserts in cabinets. The description of the products are as follows:

- **Paper or Vinyl Laminated Particleboard Panels:** Panels are composed of cellulosic particles bonded together to form sheets 0.50-inch to 0.75-inch thick (12.7 mm to 19.1 mm). Panels are listed for non-structural use only and are available in 49 inches by 97-inches (1245 mm by 2464 mm) sheets which may be finished on one or two sides with a pre-decorated paper or vinyl covering. Pre-decorated paper finish is available in 30g to 80g (44 g/m<sup>2</sup> to 118 g/m<sup>2</sup>) thicknesses, and pre-decorated vinyl finish is available in 4 mil to 73 mil (0.106mm to 1.78 mm) thicknesses. Panels have a Radiant Panel Index of 200 or less when tested in accordance with ASTM E162.
- **Paper or Vinyl Laminated Industrial Panels with MDF Core:** Panels have thicknesses between 0.125-inch to 0.75-inch (3.2 mm to 19.1 mm) and have a Radiant Panel Index of 200 or less when tested in accordance with ASTM E162.

Findings: The product is limited to the fire protection requirements under 24 CFR §3280.203. See Table 1 for scope of certification based on interior finish material.

#### Identification:

1. Each product is identified based on the manufacturer's name (Clayton Supply of Haleyville I), a plant identifier and date of production / lot number, the product name, the panel thickness, ICC-ES listing number (ESL-1344), and when applicable, the ICC-ES listing mark. The following statements are also included based on product type:

For Laminated Particleboard and Laminated Industrial Panel with MDF Core Interior Finish Products:  
Radiant Panel Index ≤ 200, when tested in accordance with ASTM E162.

- The report holder's contact information is the following:

**CLAYTON SUPPLY OF HALEYVILLE I  
 301 OLD HAMILTON ROAD  
 HALEYVILLE, ALABAMA 35564**

**Installation:** The product must be installed in accordance with Clayton Supply of Haleyville I's published installation instructions and applicable standards.

**Conditions of Listing:**

- The listing report addresses only conformance with the standard noted above.
- Approval of the product's use is the sole responsibility of the local code official.
- The listing report applies only to the materials tested and as submitted for review by ICC-ES.
- Details related to incorporation of the products are outside the scope of this listing report and are the responsibility of a registered design professional.
- The product is manufactured under a quality control program with inspections by ICC-ES.

**Table 1—SCOPE OF CERTIFICATION**

<b>INTERIOR FINISH MATERIAL</b>	<b>ASTM E162</b>
Paper or Vinyl Laminated Particleboard	Radiant Panel Index ≤200
Paper or Vinyl Laminated MDF Industrial Panels	Radiant Panel Index ≤200