



ICC-ES Listing Report ESL-1537

Rescued March 2025

This listing is subject to renewal March 2026.

CSI: DIVISION: 07 00 00-THERMAL AND MOISTURE PROTECTION
Section: 07 46 33-Plastic Siding

Product Certification System:

The ICC-ES product-certification system includes evaluating report of tests of standard manufactured product, prepared by accredited testing laboratories and provided by the listee to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the listee's quality system.

Product: CERTAINTEED CEDAR IMPRESSIONS® POLYMER SHAKE AND SHINGLE SIDING

Listee: CERTAINTEED LLC.

Compliance with the following standard:

- ASTM D7254-17, Standard Specification for Polypropylene (PP) Siding, ASTM International

Compliance with the following building code:

CertainTeed Cedar Impressions® Polymer Shake and Shingle Siding has met the physical requirements in Section 5 of ASTM D7254-17, as referenced in the applicable sections of the following code editions.

- *National Building Code of Canada® 2020*
Applicable Section: Volume 2- Division B:9.27.13.1.(1)

Description of product:

The Cedar Impressions® Polymer Shake and Shingle sidings are molded into siding panels or individual shingles from polypropylene (PP) resins. The accessory items, used to detail the application of the product as an exterior wall covering, are of the same material except for the starter strips, which are steel and aluminum.

All siding panels and individual shingles have an upper nailing flange with 1-inch-by-³/₁₆-inch (25.4 mm by 4.8 mm) elongated nail slots spaced 1½ inches (38.1 mm) on center and a lower locking leg that hooks into the upper edge of the lower course. The nailing flange has a ¹/₈-inch (3.2 mm) nail hole at the center of the panel. All panels also have side lock tabs.

The siding panels and individual shingles are available in different colors with varying shingle shapes and wood-grain textures. Siding panels and individual shingles range in nominal nail flange thickness from 0.090 inch to 0.125 inch (2.3 mm to 3.2 mm). The siding panels have lengths of 32 inches to 73½ inches (813 mm to 1867 mm). The individual shingles have lengths of 4 inches to 8 inches (102 mm to 203 mm). The accessory shapes include inside/outside corners, cornice moldings, receivers and starter strips. Refer to Table 1 and Figure 1 for panel thicknesses, lengths and profiles within the scope of this listing.

Wind Resistance:

See Table 1 for the standard wind load design pressure ratings of CertainTeed Cedar Impressions® Polymer Shake and Shingle Siding in accordance with Section 5.4.2 of ASTM D7254-17.

The siding panel must be installed only on exterior walls covered by a solid sheathing capable of supporting the imposed loads, including but not limited to positive and negative transverse wind loads.

Installation:

The siding must be installed in accordance with the CertainTeed LLC.'s published installation instructions and conform to the attachment requirements in Subsection 9.27.5 of the *National Building Code of Canada*® 2020.

The sheathing must be covered with a sheathing membrane as required in Subsection 9.27.3 of the *National Building Code of Canada*® 2020. Flashing must be provided at all openings, penetrations, and abutments with dissimilar materials, in accordance with Subsection 9.27.3.7 and 9.27.3.8 of the *National Building Code of Canada*® 2020.

Siding panels and individual shingles must be attached to sheathing substrate with galvanized, or stainless steel ring shank roofing nails with length 1½ inches or 1⅝ inches (38 mm or 41 mm), a steel shank diameter of ⅛-inch (3.18 mm), and a ⅜-inch or 7/16-inch diameter (9.5 mm or 11.1 mm) head.

The siding panel must be installed over the sheathing substrate in accordance with the applicable code. The siding panel and accessories must be fastened to framing having a minimum specific gravity of 0.42, or structural sheathing, with roofing nails with a minimum embedment into framing of ¾ inch (19.1 mm). When fastening to structural sheathing, nail penetration must be at least ¾ inch (19.1 mm) beyond the backside of the sheathing.

Accessory materials such as corners, starter strips and trim must be fastened in accordance with the manufacturer's instructions, with the starter strip fastened similar to the siding panel.

Identification:

1. The ICC-ES mark of conformity, electronic labeling, or the listing report number (ICC-ES ESL-1537), and when applicable, the ICC-ES listing mark, along with the name, registered trademark, or registered logo of the listee must be included in the product label.
2. In addition, the siding panels and shingles described in this listing are identified by a stamp bearing the manufacturer's name (CertainTeed), the product name and code, and the statement "Conforms to ASTM Specification D7254".
3. The report holder's contact information is the following:

CERTAINTEED LLC
20 MOORES ROAD
MALVERN, PENNSYLVANIA 19355
(800) 233-8990
www.certainteed.com


Conditions of listing:

1. The listing addresses only conformance with the standards and code sections noted above.
2. Approval of the product's use is the sole responsibility of the local code official.
3. The listing applies only to the materials tested and as submitted for review by ICC-ES.
4. The siding panels and shingles are limited to the maximum design wind pressures shown in Table 1.
5. The siding panels and shingles are manufactured in McPherson, Kansas, under a quality control program with inspections by ICC-ES.

TABLE 1—CEDAR IMPRESSIONS POLYMER SHAKE AND SHINGLE SIDING

| PRODUCT NAME | PRODUCT CODE | STYLE | NAILING FLANGE THICKNESS (inch) | LENGTH (inches) | FASTENER SPACING (inches) | STANDARD WIND LOAD DESIGN PRESSURE ¹ (psf) |
|--|--------------|---|---------------------------------|---------------------|---------------------------|---|
| Individual 5-inch Sawmill Shingles | 30146 | Individual 5-inch Shingles | 0.090 | Varies ² | Staples ³ | 231 |
| Triple 5-inch Straight Edge Sawmill Shingles | 30106 | Triple 5-inch Shingles | 0.100 | 60 | 10 | 43 |
| Single 6 ¹ / ₃ -inch Perfection Shapes Scallop | 30147 | Single 6 ¹ / ₃ -inch Shingles | 0.090 | 42 | 8 | 117 |
| Single 6 ¹ / ₃ -inch Perfection Shapes Octagon | 30148 | Single 6 ¹ / ₃ -inch Shingles | 0.090 | 42 | 8 | 102 |
| Single 6 ¹ / ₃ -inch Perfection Shapes Half-Cove | 30149 | Single 6 ¹ / ₃ -inch Shingles | 0.090 | 42 | 8 | 114 |
| Single 7-inch Perfection Shingles | 30137 | Single 7-inch Shingles | 0.090 | 73.5 | 10 | 105 |
| Double 7-inch Straight Edge Perfection Shingles 3G | 30144 | Double 7-inch Shingles | 0.090 | 48 | 8 | 65 |
| Double 7-inch Staggered Perfection Shingles | 30143 | Double 7-inch Shingles | 0.100 | 48 | 8 | 89 |
| Double 7-inch Straight Edge Rough-Split Shakes | 30141 | Double 7-inch Shingles | 0.125 | 57 | 10 | 59 |
| Double 9-inch Staggered Edge Rough-Split Shakes | 30136 | Double 9-inch Shakes | 0.125 | 57 | 10 | 37 |


For SI: 1 inch = 25.4 mm

NOTES:¹Standard wind loads as determined per A1.2.1 of ASTM D7254.²Individual 5-inch Straight Edge Sawmill Shingles are available in 4-inch, 4¹/₄-inch, 5-inch, 5³/₄-inch, 6³/₄-inch and 8-inch lengths.³Individual 5-inch Straight Edge Sawmill Shingles fasteners are no. 16 gage staples with a minimum length of 1¹/₂ inch (38 mm) and a crown width of ⁷/₁₆ inch (11.1 mm), spaced ³/₄ inch (19.1 mm) from each shingle edge into the sheathing.


Individual 5-inch Sawmill Shingles



Triple 5-inch Straight Edge Sawmill Shingles

Single 6¹/₃-inch Perfection Shapes ScallopSingle 6¹/₃-inch Perfection Shapes OctagonSingle 6¹/₃-inch Perfection Shapes Half-Cove

Single 7-inch Perfection Shingles



Double 7-inch Straight Edge Perfection Shingles 3G



Double 7-inch Staggered Perfection Shingles



Double 7-inch Straight Edge Rough-Split Shakes



Double 9-inch Staggered Edge Rough-Split Shakes

FIGURE 1—PRODUCT PROFILES