



CSI: DIVISION: 22 00 00 – PLUMBING  
Section: 22 13 16 – Sanitary Waste and Vent Piping

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: EZ-Flex Couplings

Listee: ProVent Systems, a division of IPS Corporation  
500 Distribution Parkway  
Collierville, Tennessee 38017  
[www.proventsystems.com](http://www.proventsystems.com)

Compliance with the following codes:

2024, 2021, 2018, 2015, 2012 and 2009 *International Plumbing Code® (IPC)*  
2024, 2021, 2018, 2015, 2012 and 2009 *International Residential Code (IRC)*  
2024, 2021, 2018, 2015, 2012 and 2009 *Uniform Plumbing Code® (UPC)\**

*\* Copyrighted publication of the International Association of Plumbing and Mechanical Officials*

Compliance with the following standards:

ASTM C1173-2022, Flexible Transition Couplings for Underground Piping Systems  
CSA B602-20, Mechanical Couplings for Drain, Waste, and Vent Pipe and Sewer Pipe

Identification:

Couplings shall be permanently marked with the manufacturer's name or the manufacturer's registered trademark, model number, nominal pipe size (NPS), pipe material(s) for which the coupling is designed, standard designation, and ICC-ES PMG listing mark.

Models:

**EZ-Flex Coupling**

EZ Flex Couplings are designed for the connection of PVC to PVC and PVC to Cast Iron DWV and sewer pipe.

EZ-Flex coupling consists of a one-piece elastomeric polyvinyl chloride (PVC) gasket with a 300 series stainless steel clamp. The male end is solvent cemented to the rigid coupling; the female end is connected with either PVC or cast iron pipe with sealing by mechanical clamp.

**Table 1 – EZ FLEX COUPLINGS**

<b>Part Number</b>	<b>Description</b>
P1514	1-1/2" PVC to 1-1/4" TUBULAR
P15470	1-1/2" PVC to 1-1/2" TUBULAR
P25470	2" E-Z FLEX COUPLING
P35470	3" E-Z FLEX COUPLING
P35470-D	3" E-Z FLEX DOUBLE COUPLING
P45470	4" E-Z FLEX COUPLING
P45470-D	4" E-Z FLEX DOUBLE COUPLING
P65470	6" E-Z FLEX COUPLING

1 inch = 25.4 mm

Conditions of Listing:

1. The EZ Flex Couplings must be installed in accordance with this listing, the applicable code and the manufacturer's published installation instructions. The instructions within this listing must govern if there are any conflicts between the manufacturer's published instructions and this listing.
2. Use of EZ Flex couplings above ground is subject to the approval of the code official.
3. Couplings are under a quality control program with annual inspections by ICC-ES.