



CSI: DIVISION: 22 00 00—PLUMBING  
Section: 22 09 00—Instrumentation and Control for Plumbing

### Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: Plumbing Supply Fittings

Listee: Symmons Industries, Inc.  
31 Brooks Dr.  
Braintree, MA 02184  
[www.symmons.com](http://www.symmons.com)

### Compliance with the following codes:

2024, 2021, 2018, 2015, 2012 and 2009 *International Plumbing Code*® (IPC)  
2021, 2018, 2015, 2012 and 2009 *International Residential Code*® (IRC)  
2024, 2021, 2018, 2015, 2012 and 2009 *Uniform Plumbing Code*® (UPC)\*  
2020, 2015, 2010 and 2005 *National Plumbing Code of Canada*® (NPC)\*\*  
*2017 Uniform Illustrated Plumbing Code – India (UIPC-India)\**

\* Copyrighted publication of the International Association of Plumbing and Mechanical Officials

\*\* Copyrighted publication of National Research Council Canada

### Compliance with the following standards:

ASME A112.18.1/CSA B125.1-2018 (R2023), Plumbing Supply Fittings  
NSF/ANSI/CAN 61-2022 Drinking Water System Components – Health Effects

### Identification:

Plumbing Supply fittings shall be marked with:

- a) The manufacturer's recognized name, trademark, or other mark; or
- b) In the case of private labeling, the name, trademark, or other mark of the customer for whom the fitting was manufactured.
- c) The ICC-ES PMG listing mark

Shower heads and hand-held showers shall be marked with the manufacturer's specified maximum flowrate, in L/min and gpm.

Markings shall be accomplished by use of a permanent mark or by placing a permanent label on the product. Markings shall be located in such a way that they are visible after installation.

Packaging shall be marked with:

- a) The manufacturer’s recognized name, trademark, or other mark as well as the model number; or
- b) In the case of private labeling, the name, trademark, or other mark of the customer for whom the fitting was manufactured as well as the model number.

Packaging or other included literature for shower heads and hand-held showers shall be marked with

- a) the manufacturer’s specified maximum flow rate determines through testing.
- b) the statement “For use with automatic compensating valves rated at xxx L/min (yyy gpm) or less”, where xxx L/min (yyy gpm) is the lowest minimum flow rate.

Installation:

Plumbing Supply fittings shall be installed in accordance with the manufacturer's instructions and the applicable codes.

Models:

The following Lavatory Faucet model complies with ASME A112.18.1/CSA B125.1 and NSF/ANSI 61.

Model Number	Description
S-6710-PD	Kitchen Faucet
S-6710-PD-STS-Z	Kitchen Faucet
S-6080-Y	Ultra-Sense Sensor Faucet
S-6098-Y	Ultra-Sense Sensor Faucet
SLW-3522-X-1.5	Lavatory Faucet, Widespread, Dia Short Spout
SLW-0600-BODY	Widespread Lavatory Faucet, Body
SLW-0600-12-1.0-TRM	Widespread Lavatory Faucet, Trim
SLW-0600-BODY	Widespread Lavatory Faucet, with lever handles, Body
SLW-0600-12-1.0-ADA-TRM	Widespread Lavatory Faucet, with lever handles, Trim
SPB-3510-Z	Single Handlebar Kitchen Faucet
SPB-3510-STN-Z	Single Handlebar Kitchen Faucet
SWM-4310-1.5	Sereno Two Handle Wall Mounted Lavatory Faucet
SWM-4310-STN-1.5	Sereno Two Handle Wall Mounted Lavatory Faucet
CDSWM1333-4310-1.5	Sereno Two Handle Wall Mounted Lavatory Faucet
CDSLW163012CYLBMB12	Lavatory Faucet

“X” represents various handles available (blank, H2, H3)

“Y” represents additional options (blank, -0.5, -12V-SSUP-G, -AC-12V, -AC-12V-SSUP, -AC-12V-SSUP-G, -ACM-12V, AMC-12V-G, -G, -ACM-12V-SSUP-G, -SSUP, -SSUP-0.5, SSUP-G, -SSUP-G-0.35)

“Z” represents various flow rates (gpm) available (-2.2, -1.5, -1.2, -1.0, -0.5)

The following Showerhead and Handheld Shower models comply with ASME A112.18.1/CSA B125.1.

Model Number	Description
4-143-*	Showerhead, 3 Mode
4-241-*	Showerhead, 1 Mode
EF-100-*	Hand Shower Wand, 1 Mode
H301-V-*	Hand Shower Assembly, 1 Mode, Less Bar
EF-101-*	Hand Shower Wand, 3 Mode
H303-V-*	Hand Shower System, 3 Mode, Less Bar
H323-V-*	Hand Shower System, 3 Mode, With Bar
EF-118-*	Hand Shower Wand, 1 Mode
H421-V-*	Hand Shower System, 1 Mode, With Bar
EF-119-*	Hand Shower Wand, 3 Mode

H403-V-*	Hand Shower System, 3 Mode, Less Bar
H423-V-*	Hand Shower System, 3 Mode, With Bar
462W-*	Hand Shower Wand, 1 Mode
H501-V-*	Hand Shower System, 1 Mode. Less Bar
H521-V-*	Hand Shower System, 1 Mode. With Bar
CDS0421-3504CYL1.5ETCHTRM	Ronald McDonald House, Hand Shower System, 1 Mode with bar, 1.5 GPM
CDS0421-3503CYL1.5ETCHTRM	Ronald McDonald House, Hand Shower System, 1 Mode with bar, 1.5 GPM

*Asterisk represents the various maximum flow rates available (2.5 gpm, 2.0 gpm, 1.5 gpm)*

Conditions of listing:

1. The Symmons' products recognized in this listing must be installed in accordance with the manufacturer's published installation instructions and the applicable codes.
2. The Symmons' products recognized in this listing are under a quality control program with annual surveillance inspections by ICC-ES.