

ICC-ES PMG Product Certificate



PMG-1399

Effective Date: September 2024 This listing is subject to re-examination in one year.

www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING

Section: 22 40 00—Plumbing Fixtures

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality

system

Product: Water Closet, Vitreous China

Chaozhou Boling Smart Sanitary Wares Co. Ltd. Listee:

> Yong'An Economic Zone, GuXiang Chaozhou, Guangdong China www.casabathroom.com

Additional Listee:

THNIKRE INC S 5142 N Academy Blvd. Unit 1040 Colorado Springs, CO 80918 **United States**

Compliance with the following standards:

EPA WaterSense Tank-Type High Efficiency Toilet Specification (version 2.0)

Identification:

Each fixture or fixture component must be permanently and legibly marked with the manufacturer's name or registered trademark, model number and the date of manufacture. Gravity flush tanks shall be permanently marked with a water level mark. Water closets shall be marked with the water consumption in GPF and LPF and the EPA WaterSense logo and the ICC-ES PMG listing mark. All packaging must be marked with the manufacturer's name or registered trademark; or in case of private labeling, the name of the customer for whom the fixture was manufactured. Packaging for water closets and urinals shall be marked with the water consumption in GPF and LPF.

Installation:

Water Closets are to be installed in accordance with the manufacturer's instructions and the applicable code. A water closet shall not be set closer than 15 inches (381 mm) from its center to any side wall, partition, vanity, or other obstruction, or closer than 30 inches (762 mm) center to center between adjacent fixtures. There shall be not less than a 21-inch (533 mm) clearance in front of the water closet to any wall, fixture, or door. Water closet compartments shall be not less than 30 inches (762 mm) in width and not less than 60 inches (1524 mm) in depth for floor- mounted water closets and not less than 30 inches (762 mm) in width and 56 inches (1422 mm) in depth for wall- hung water closets.



Models:

Chaozhou Boling Smart Sanitary Wares Co. Ltd.

Brand Name: CASA

Certification Date	Model Name	Model Number	Bowl Model Number	Tank Model Number	Flush Type	Flush Mechanism	Rated Flush Volume (single or avg) gpf	Rated Flush Volume (Full Flush) gpf	Rated Flush Volume (Reduced Flush) gpf
09/01/16		BL101			Single	Gravity	1.28		
09/01/16		BL103			Single	Gravity	1.28		
09/01/16		BL108			Single	Gravity	1.28		

Brand Name: LA FONZA

Certification Date	Model Name	Model Number	Bowl Model Number	Tank Model Number	Flush Type	Flush Mechanism	Rated Flush Volume (single or avg) gpf	Rated Flush Volume (Full Flush) gpf	Rated Flush Volume (Reduced Flush) gpf
09/01/16		BL101			Single	Gravity	1.28		
09/01/16		BL103			Single	Gravity	1.28		
09/01/16		BL108			Single	Gravity	1.28		

Additional Listee Models:

THNIKRE INC

Brand Name: THNIKRE

Certification Date	Model Name	Model Number	Bowl Model Number	Tank Model Number	Flush Type	Flush Mechanism	Rated Flush Volume (single or avg) gpf	Rated Flush Volume (Full Flush) gpf	Rated Flush Volume (Reduced Flush) gpf
12/03/21		DL-BL101			Single	Gravity	1.28		
12/03/21		DL-BL103			Single	Gravity	1.28		
12/03/21		DL-BL108			Single	Gravity	1.28		

Conditions of Listing:

- The water closet models recognized in this listing must be installed in accordance with the manufacturer's published installation instructions and the applicable code.
 The water closet models recognized in this listing are under a quality control program with annual surveillance inspections by ICC-ES.