

*Effective Date: June 2024**This listing is subject to re-examination in one year.*[www.icc-es-pmg.org](http://www.icc-es-pmg.org) | (800) 423-6587 | (562) 699-0543*A Subsidiary of the International Code Council®*

CSI: DIVISION: 22 00 00—PLUMBING  
Section: 22 40 00—Plumbing Fixtures

**Product certification system:**

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: LOXCREEN Drains

Listee: LOXCREEN CANADA LTD.  
5720 Ambler Drive  
Mississauga, Ontario, Canada L4W 2B1  
[www.loxcreenflooring.com](http://www.loxcreenflooring.com)

**Compliance with the following codes:**

2024, 2021, 2018, 2015, 2012, 2009 and 2006 *International Plumbing Code®* (IPC)  
2024, 2021, 2018, 2015, 2012, 2009 and 2006 *International Residential Code®* (IRC)  
2024, 2021, 2018, 2015, 2012, 2009 and 2006 *Uniform Plumbing Code®* (UPC)\*  
2024, 2021, 2018, 2015, 2012 and 2009 *National Standard Plumbing Code* (NSPC)  
2022, 2019, 2016, 2013 and 2010 *California Plumbing Code* (CPC)  
2023, 2020 and 2017 *City of Los Angeles Plumbing Code*  
2023, 2021, 2017 and 2007 *Code of Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code*  
2022 and 2017 *Uniform Illustrated Plumbing Code – India™* (UIPC-I)\*  
2020, 2015 and 2010 *National Plumbing Code of Canada®* (NPC)\*\*

\*Copyrighted publication of the International Association of Plumbing and Mechanical Officials

\*\* Copyrighted publication of the National Research Council Canada

**Compliance with the following standards:**

ASME A112.18.2/CSA B125.2-2020, Plumbing Waste Fittings

**Identification:**

Each LOXCREEN Drains described in this listing must be identified by a label bearing the manufacturer's name, model number, and the ICC-ES PMG listing mark.

**Installation:**

LOXCREEN Drains are suitable for use with tile showers. The clamping ring or waterproofing membrane and the connection to the drain line must be installed in accordance with the manufacturer's published instructions and the applicable codes.

Ceramic tile, if used, must comply with ANSI A137.1.

Waterproofing membrane, if used, must comply with the applicable code or ANSI A118.10 and must be fastened to the top surface of the drain with an adhesive. This is attached at the jobsite. Clamping Ring, if used, must comply with the applicable code or ASME A112.18.2/CSA B125.2 and must be installed in accordance with manufacturer's installation instructions.

**Models:**

Linear Shower Drain model # TT8900TNTXX comprised of the following components:

1. Drain Body (XISD8900DBXX)
2. Stainless Steel Grate (XISD8900DGXX)
3. ABS Tops and Attachments (XISD8900TIDGXX)

XX represents different lengths of 24, 32, 36, 42, 48, 54, 60 (in inches)

**Conditions of Listing:**

1. Shower floors must be sloped toward the drain.
2. Where each shower space is not provided with an individual waste outlet, the waste outlet must be located, and the floor pitched so that waste from one shower does not flow over the floor area serving another shower.
3. Application is limited to ceramic tile, decorative concrete, granite slab and dimension stone installations on floors, and to use as shower sub-pans or lining.
4. Documentation of the waterproof membrane's conformance with ANSI A118.10 must be supplied to the code official when requested, or the membrane must have a current listing by ICC-ES.
5. Documentation of the clamping ring's conformance with ASME A112.18.2/CSA B125.2 must be supplied to the code official when requested, or the clamping ring must have a current listing by ICC-ES.
6. Where installation is below the floor decking, the drain can be oriented parallel or perpendicular to any floor joists. Cutting or notching must be in accordance with the applicable code.
7. The LOXCREEN Drains are manufactured under a quality control program with one inspection per year by ICC-ES.