



Effective Date: September 2024

This listing is subject to re-examination in one year.

www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING
Section: 22 13 16—Sanitary Waste and Vent Piping

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: Barrier Trap Seal Devices for Floor Drains

Listee: IPS Corporation
500 Distribution Parkway
Collierville, Tennessee 38017
www.ipscorp.com

Additional Listee:

Hajoca Corporation dba Mainline
6232 Siegen Lane
Baton Rouge, LA 70809
United States
225-295-4212
www.mainlinecollection.com

Compliance with the following codes:

2024, 2021, 2018, 2015, 2012, 2009 and 2006 *International Plumbing Code*® (IPC)
2024, 2021, 2018, 2015, 2012, 2009 and 2006 *International Residential Code*® (IRC)
2024, 2021, 2018, 2015, 2012, 2009 and 2006 *Uniform Plumbing Code*® (UPC)*
2022 *Illustrated Uniform Plumbing Code – India*® (UPC-I)*
2020, 2015, 2010 and 2005 *National Plumbing Code of Canada*® **

*Copyrighted publication of the International Association of Plumbing and Mechanical Officials

**National Plumbing Code of Canada is a copyrighted publication of National Research Council Canada

Compliance with the following standards:

ASSE 1072-2020, Performance Requirements for Barrier Type Floor Drain Trap Seal Protection Devices, American Society of Sanitary Engineering
CSA B79-2008 (R18), Floor, Area and Shower Drains, and Cleanouts for Residential Construction
ICC-ES LC1015, PMG Listing Criteria for Elastomeric, Normally Closed, Floor Drain Evaporation Resistant Sealing System (Oct 2010)

Identification:

The product and/or package must bear the manufacturer's name, the model number and the ICC-ES PMG listing mark.

Installation:

The Trap Tite™ Trap Seal devices are to be installed in accordance with the manufacturer's instructions and the applicable code.

Models:**Trap Tite™ Trap Seal**

<u>MODEL</u>	<u>Device Size</u>		<u>Flow Rate</u>	
	<u>Inches</u>	<u>mm DN</u>	<u>GPM</u>	<u>L/M</u>
69420	2	51	12.0	45.4
69430	3	76	34.0	128.7
69435	3.5	89	52.0	196.8
69440	4	102	73.0	276.3

Additional Listee Models:**MAINLINE Waterless Trap Seal**

<u>MODEL</u>	<u>Device Size</u>		<u>Flow Rate</u>	
	<u>Inches</u>	<u>mm DN</u>	<u>GPM</u>	<u>L/M</u>
ML69020	2	51	12.0	45.4
ML69030	3	76	34.0	128.7
ML69035	3.5	89	52.0	196.8
ML69040	4	102	73.0	276.3

Conditions of listing:

1. The IPS Corp. models recognized by this listing, are intended to serve as alternates to the code-required trap primer. They must serve a functioning trap.
2. The plumbing systems must be installed in accordance with the applicable codes and must be accessible.
3. The IPS Corp. devices are manufactured under a quality control program with annual surveillance inspections.