



# ICC-ES PMG Product Certificate

# PMG-1680



Effective Date: August 2024

This listing is subject to re-examination in one year.

[www.icc-es-pmg.org](http://www.icc-es-pmg.org) | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING  
Section: 22 13 16—Sanitary Drain, Waste and Vent Piping

### Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: FloFX Shower Drains and Waterproofing Membrane

Listee: FloFX, LLC  
423 W. Coal Creek Road, Ste. #1  
Cedar City, Utah 84721  
[www.flofx.com](http://www.flofx.com)

### Compliance with the following codes:

- 2024, 2021, 2018, 2015, 2012, 2009 and 2006 *International Residential Code*® (IRC)
- 2024, 2021, 2018, 2015, 2012, 2009 and 2006 *International Plumbing Code*® (IPC)
- 2024, 2021, 2018, 2015, 2012, 2009 and 2006 *Uniform Plumbing Code*® (UPC)\*
- 2022, 2019, 2016, and 2013 *California Plumbing Code* (CPC)\*
- 2022, 2019, 2016, and 2013 *California Residential Code* (CRC)
- 2023, 2020 and 2017 *City of Los Angeles Plumbing Code*
- 2023, 2021, 2017 and 2007 *Code of Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code*
- 2022 *Uniform Illustrated Plumbing Code*® - India (UIPC-I)\*
- 2020, 2015 and 2010 *National Plumbing Code of Canada*® \*\*

\*Copyrighted publication of the International Association of Plumbing and Mechanical Officials

\*\*National Plumbing Code of Canada is a copyrighted publication of National Research Council Canada

### Compliance with the following standards:

- ASME A112.18.2/CSA B125.2-2020, Plumbing Waste Fittings
- TCNA/ANSI A118.10-2023, Load Bearing, Bonded, Waterproofing Membranes for Thin-Set Ceramic Tile and Dimension Stone Installation

### Identification:

Each Drain described in this listing must be identified by a label bearing the manufacturer's name, trench length, and the ICC-ES PMG listing mark.

*Listings are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the listing or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this listing, or as to any product covered by the listing.*



**Installation:**

The FloFX Shower Drains are suitable for use with tile showers. The shower drain, bonding flange, and the connection to the drain line must be installed in accordance with the manufacturer's published instructions, the applicable codes and Tile Council of North America Guidelines.

Ceramic tile, if used, must comply with ANSI A137.1.

Waterproofing membrane, if used, must comply with the applicable code or TCNA/ANSI A118.10 and must be joined to the bonding flange of the drain with a manufacturer approved sealant. This is attached at the jobsite.

**Models:**

The FloFX drain bodies and bonding flange are fabricated from either ABS or PVC material. Connection to the waste line is a solvent welded joint.

FloFX NOFLO is a Waterproofing Membrane that is compliant with TCNA/ANSI A118.10

Strainers are available in different designs and sizes to match the drain bodies.

Drain Bodies

ABS Bond Flange Kit  
ABS Traditional Bond Flange Kit  
ABS Universal Bond Flange Kit  
PVC Bond Flange Kit  
PVC Traditional Bond Flange Kit

Grates

Blank Slate  
Classic <sup>2</sup>  
Clean Lines  
FloFX Tile-in Grate  
HEX3D  
Modern Retro  
RADius 3D  
X Factor

**Conditions of Listing:**

1. Shower floors must be sloped toward the drain.
2. Where each shower space is not provided with an individual waste outlet, the waste outlet must be located, and the floor pitched so that waste from one shower does not flow over the floor area serving another shower.
3. Application is limited to ceramic tile, decorative concrete, granite slab and dimension stone installations on floors, and to use as shower sub-pans or lining.
4. Where installation is below the floor decking, the drain can be oriented parallel or perpendicular to any floor joists. Cutting or notching must be in accordance with the applicable code.
5. The FloFX Shower Drains recognized in this listing are under a quality control program with an annual surveillance inspection per year by ICC-ES.